

THE BEST IN THE BUSINESS



- X-Factor® II Deck The 7-gauge, all-steel welded X-Factor® II Deck is fabricated from top to bottom, providing industrial-strength peace of mind that's reinforced with an exclusive limited lifetime warranty.
- Air-Ride Suspension Seat The industry's first air-ride suspension system is enhanced with seat isolators to absorb large vertical impacts and designed with an oversized, pillow-top, extra high-back seat for all-day comfort.
- **CBT System** Our exclusive Constant Belt Tension System (CBT) ensures that belt tension is constant, keeping the blade tip speed and cutting results consistent.
- **EZ-Lift™ Deck System** The ES-Lift Deck System takes 25% less effort to raise and lower the deck. Plus, 19 cutting positions with .25-inch increments help eliminate overhung loads.
- **Steel Chassis** A heavy duty 1.5-inch x 3-inch steel, singular tubular frame is fabricated with four engine frame isolation points to reduce cockpit vibration by 45% while lessening operator fatigue.
- Radial Rear Tires Radial rear tires come standard, delivering automotive-style performance, industryleading handling and hill holding, while being gentler to the turf.

1 10-	1 U K N 4 U U										
	PRODUCT NAME	Pro-Turn 452	Pro-Turn 452	Pro-Turn 460	Pro-Turn 460	Pro-Turn 460	Pro-Turn 460	Pro-Turn 472	Pro-Turn 472	Pro-Turn 460	
	MODEL NUMBER	992273	992282/ 992289*	992274	992275	992278	992283/ 992288*	992276	992284/ 992290*	992280*	
		Kawasaki® FX850	Yamaha EFI MXV775	Kawasaki® FX921V	Kawasaki® FX1000V	Kohler EFI ECV880	Yamaha EFI MXV825	Kawasaki® FX1000V	Yamaha EFI MXV825	Kohler PCV860 EFI	
	ENGINE	Air-cooled	Air-cooled	Air-cooled	Air-cooled	Air-cooled	Air-cooled	Air-cooled	Air-cooled	"Air-cooled	
		Vertical twin"	Heavy-Duty Air Cleaner								
	HORSEPOWER (HP)	27	29	31	35	33	33	35	33	29	
	DISPLACEMENT (CC)	852	824	999	999	824	824	999	824	824	
	DRIVE SYSTEM	Hydro-Gear® ZT-5400 Integrated pump/motor									
	FUEL CAPACITY - GALLONS (LITERS)	13.4 (50.7)	13.4 (50.7)	13.4 (50.7)	13.4 (50.7)	13.4 (50.7)	13.4 (50.7)	13.4 (50.7)	13.4 (50.7)	Twin 33.5# tanks (tanks not included)	
ı	GROUND SPEED (APPROX. MPH) (FOR/REV)					13 mph/6 mph					
DECK	DECK MATERIAL	7 ga steel with .25 inch spindle reinforcement									
	DECK CONSTRUCTION	Welded	Welded	Welded	Welded	Welded	Welded	Welded	Welded	Welded	
	NUMBER OF SPINDLES		3	3	3	3	3	3	3	3	
	BLADE TIP SPEED (FPM)	18,348	18,348	18,633	18,633	18,633	18,633	18,229	18,229	18,633	
	SPINDLE MATERIAL					Cast Iron					
	SPINDLE BEARINGS	Ball Bearing									
	DECK ENGAGEMENT	Ogura® GT3.5 Electric Clutch									
	CUTTING WIDTH (INCHES)	52"	52"	60"	60"	60"	60"	72"	72"	60"	
	CUTTING HEIGHTS (INCHES)	1.0-5.5"	1.0-5.5"	1.0-5.5"	1.0-5.5"	1.0-5.5"	1.0-5.5"	1.0-5.5"	1.0-5.5"	1.0-5.5"	
	CUTTING POSITIONS	19	19	19	19	19	19	19	19	19	
WHEELS											
	FRONT AXLE	Fixed with greaseable caster fork tubes									
	FRONT (INCHES)	Smooth 15 x 6-6 Semi Pneumatic									
1	REAR (INCHES)	Radial Turf 23x10-12	Radial Turf 24x12-12								
FEATURE	S										
	SEAT	High Back w/ Full Air Ride Suspension and seat isolators									
	HOOD	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
ı	FOLDABLE ROPS	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
MACHIN	E DIMENSIONS										
	WEIGHT (LBS) W/O FUEL	1326	1332	1358	1358	1360	1356	1453	1445	1579	
	LENGTH (INCHES)	80"	80"	80"	80"	80"	80"	82	80"	80"	
	WIDTH (INCHES) (W/O CHUTE)	55.5"	55.5"	63"	63"	63"	63"	75"	75"	63"	
	WIDTH W/ CHUTE	67.75"	67.75"	75.25"	75.25"	75.25"	75.25"	87.25"	75.25"	75.25"	
1	HEIGHT W/ ROPS EXT/ DOWN (INCHES)	70/47.75"	70/47.75"	70/47.75"	70/47.75"	70/47.75"	70/47.75"	70/47.75"	70/47.75"	70/47.75"	
WARRAN	ITY										
	UNIT				3	Year Limited Commerc	ial				
	DECK SHELL & FRAME	HELL & FRAME Limited Lifetime Deck Shell & Frame									
	SPINDLES	3 Year Limited Spindle									