



**Tornado**  
HOPPER SPREADER



**The next storm is in your control.** For exceptional, CONTRACTOR GRADE® ice control, turn to the WESTERN® Tornado™ hopper spreader. Now built to put more control at your fingertips, the Tornado hopper spreader delivers efficient salt and sand spreading operation through a variety of new and optimized performance features, including enhanced **dual variable-speed control, convenient accessory hub, rear dump and work light buttons** and **easy electrical disconnect for the chute**. Also designed with **FLEET FLEX** technology for easy interchange between electric hopper spreaders. More features mean **More jobs. Done faster.**

#### VARIABLE SPEED CONTROL

Enhanced dual variable-speed control allows you to precisely match material delivery and spread patterns to conditions. Four standard accessory buttons and a dedicated blast button provide optimum in-cab efficiency. Easy-to-understand, digital self-diagnostics alert the operator when the hopper is empty or when adjustments are needed, and LEDs make the controls easy to read. Its compact size compared to traditional controls fits easily into today's modern truck cab designs.



#### ACCESSORY HUB

The Tornado hopper spreader features an enclosed accessory hub for easy plug-n-play installation. Accessories automatically integrate with the hopper control without having to run additional wires from the front to the truck.



#### **FLEETFLEX** ELECTRICAL SYSTEM

Now built to put more control at your fingertips, the Tornado hopper spreader is designed with FLEET FLEX technology for easy interchange between electric hopper spreaders, without having to change the wiring or the controls.



MORE CONTROL MEANS MORE PROFITABILITY

### DUAL ELECTRIC MOTORS

Two instant-start, 12-volt electric motors provide quiet, reliable and independent control over the conveyor and spinner mechanisms. The spinner motor is sealed inside a weather-resistant housing, protecting it from corrosion and the elements.



### TWO-PIECE POLY HOPPER COVER



The overlapping poly hopper covers shield de-icing material from the elements, seal out moisture and act as spillguards to protect the truck from material overflow during loading.

### EASILY REMOVABLE UNIT

With chute removed, the unit stands on end to save storage space during the off-season.



### ONE-PIECE POLY CONSTRUCTION

The one-piece, double-walled poly hopper body and stainless steel bottom sill provide a long, corrosion-free life. Available in three sizes: 7' 1.5 cu yd, 8' 1.8 cu yd, 8' 2.5 cu yd

### NEW STANDARD FEATURES

- Accessory Hub
- Rear Dump Button
- Work Light Button
- Easy Electrical Chute Disconnect

### OTHER STANDARD FEATURES

- 16½" Pintle Chain
- Top Screen
- Built-in Tie-down Loops
- Adjustable Chute
- Adjustable Feed Gate

### OPTIONAL ACCESSORIES

- License Plate Kit
- Work Light Kit
- Strobe Light
- Vibrator Kit
- Inverted V Kit
- Hold Down Kit

#### AVAILABLE POWER OPTIONS & APPROX. WEIGHT (EMPTY)

Body Side Length	Capacity	Hopper Construction	Dimensions Overall (LxWxH)	AVAILABLE POWER OPTIONS & APPROX. WEIGHT (EMPTY)				Conveyor Width	Spinner Size	Spreading Width	Materials	Vehicle Application
				Dual 12V DC Sealed Motors	Gas 10.5 hp I/C Briggs & Stratton®	Gas 11 hp I/C Honda®	Dual Hydraulic Motors					
7' (2.13 m)	1.5 cu yd (1.15 cu m)	Polyethylene	108" x 63" x 44" (274 cm x 160 cm x 112 cm)	591 lb (268.07 kg)	—	—	—	16½" (42 cm)	15½" (40 cm)	Up to 40' (Up to 12.19 m)	Salt, Sand, Salt/Sand Mix	3/4- & 1-Ton Pickup Trucks
8' (2.44 m)	1.8 cu yd (1.38 cu m)	Polyethylene	117" x 63" x 44" (297 cm x 160 cm x 112 cm)	660 lb (299.37 kg)	—	—	—	16½" (42 cm)	15½" (40 cm)	Up to 40' (Up to 12.19 m)	Salt, Sand, Salt/Sand Mix	3/4- & 1-Ton Pickup Trucks
8' (2.44 m)	2.5 cu yd (1.91 cu m)	Polyethylene	117" x 63" x 51" (297 cm x 160 cm x 130 cm)	734 lb (332.94 kg)	—	—	—	16½" (42 cm)	15½" (40 cm)	Up to 40' (Up to 12.19 m)	Salt, Sand, Salt/Sand Mix	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)



Western Products | P.O. Box 245038 | Milwaukee, WI 53224-9538

More jobs. Done faster. | [www.westernplows.com](http://www.westernplows.com) |



Western Products reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Western Products or the vehicle manufacturer may require or recommend optional equipment for spreaders. Do not exceed vehicle rating with a spreader. This product is manufactured under the following US patents: 6,253,470; 7,400,058; 7,737,576. Western Products offers a limited warranty for all spreaders and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, LLC: PRODIGY™, Tornado™, WESTERN®.