

COMPACT SERIES

Sure it looks small. But our compact powerhouse packs a big-time punch. From a light dusting, to residential sidewalk duty, Ariens compact machines are easy to maneuver, while consistently delivering performance that's impossible to overlook. Folding handlebars make putting it away as easy as it is to use.



AUGER

11" auger diameter



TRACK

Available track system for improved traction on any terrain



ENGINE

Available electric start gets you running with ease



TIRES

16" directional tires provide improved mobility and agility







DESIGNATION	COMPACT 20	COMPACT 24	COMPACT TRACK 24
MODEL	920024	920021	920022
ENGINE	Ariens AX 208cc (9.5 ft/lbs)	Ariens AX 208cc (9.5 ft.lbs)	Ariens AX 208cc (9.5 ft/lbs)
STARTING SYSTEM	3 ft - 40 ft (.9-12.2 m)	3 ft - 40 ft (.9-12.2 m)	3 ft - 40 ft (.9-12.2 m)
DRIVE TYPE	2.5x Quick Turn	2.5x Quick Turn	2.5x Quick Turn
AUGER DIAMETER	11" (27.9 cm)	11" (27.9 cm)	11" (27.9 cm)
HOUSING	20" w x 20" h	24" w x 20" h	24" w x 20" h
TIRE SIZE	15 in x 5 in (38 x 13 cm)	15 in x 5 in (38 x 13 cm)	5.5" Wide Track
TONS / HOUR	55 tons	58 tons	58 tons

COMPACT SPECIFICATIONS

D E S I G N A T I O N	COMPACT 20	COMPACT 24	COMPACT TRACK 24
MODEL #	920024	920021	920022
STAGE TYPE	Two Stage	Two Stage	Two Stage
ENGINE POWER	208cc (9.5 ft/lbs)	208cc (9.5 ft.lbs)	208cc (9.5 ft/lbs)
ENGINE BRAND	Ariens AX	Ariens AX	Ariens AX
STARTING SYSTEM	120V/Recoil	120V/Recoil	120V/Recoil
CLEARING WIDTH	20 in (50.8 cm)	24 in (60.1 cm)	24 in (60.1 cm)
HOUSING HEIGHT	20 in (50.8 cm)	20 in (50.8 cm)	20 in (50.8 cm)
THROWING DISTANCE	3 ft - 40 ft (.9-12.2 m)	3 ft - 40 ft (.9-12.2 m)	3 ft - 40 ft (.9-12.2 m)
CHUTE TURNING RADIUS	205°	205°	205°
DEFLECTOR CONTROL	2.5x Quick Turn	2.5x Quick Turn	2.5x Quick Turn
TIRE SIZE	15 in x 5 in (38 x 13 cm)	15 in x 5 in (38 x 13 cm)	5.5" Wide Track
TIRE TYPE	Directional Snow Tread	Directional Snow Tread	Directional Snow Tread Track
STEERING	Pin Lock	Pin Lock	Solid Locked
DRIVE TYPE	Disc-O-Matic	Disc-O-Matic	Disc-O-Matic
SPEEDS	6 Forward / 2 Reverse	6 Forward / 2 Reverse	6 Forward / 2 Reverse
GEAR CASE	Cast Iron	Cast Iron	Cast Iron
GEAR CASE WARRANTY	5yr Cons, 1yr Comm	5yr Cons, 1yr Comm	5yr Cons, 1yr Comm
IMPELLER PROFILE	Steel 3 Blade	Steel 3 Blade	Steel 3 Blade
IMPELLER DIAMETER	12 in (30.5 cm)	12 in (30.5 cm)	12 in (30.5 cm)
AUGER DIAMETER	11 in (27.9 cm)	11 in (27.9 cm)	11 in (27.9 cm)
AUGER TYPE	Steel Serrated	Steel Serrated	Steel Serrated
SKID SHOES	Steel Reversible	Steel Reversible	Steel Reversible
SCRAPER BAR	Steel Adjustable	Steel Adjustable	Steel Adjustable
PRODUCT WARRANTY	3yr Cons, 90 day Comm	3yr Cons, 90 day Comm	3yr Cons, 90 day Comm
LENGTH	44.5 in (113.03 cm)	44.5 in (113.03 cm)	44.5 in (113.03 cm)
WIDTH	27 in (68.58 cm)	27 in (68.58 cm)	27 in (68.58 cm)
HEIGHT	34.25 in (86.9 cm)	34.25 in (86.9 cm)	34.5 in (87.63 cm)
WEIGHT	200 lbs (90.72 kg)	212 lbs (96.16 kg)	249 lbs (112.94 kg)
FEATURES AT A GLANCE	URES AT A GLANCE Halogen Headlight, Handwarmers (optional), Remote Deflector, Electric Start, Drift Cutters (optional), One Hand Interlock		

 $^{** \}textit{Limited quantities available}.$





Commercial-grade cast-iron gear case for extreme snow conditions provides durability, extra power and longer gear life.



Compact Series has a three-year limited warranty, excluding commercial usage.

Commercial usage carries a 90-day limited warranty

